

DUBLIN

D



AL6063 HEATSINKER FOR

BETTER LUMEN

MAINTENANCE RATE AND  
LONGER LIFESPAN.






# DUBLIN



## Parameters

Model	Power	Actual Power	Voltage	Size(mm)
HEC-TUP-26	26W	26W±10%	110-265V	615*75*25
HEC-TUP-36	36W	36W±10%	130-265V	615*75*25
HEC-TUP-54	54W	54W±10%	165-265V	1215*75*25
HEC-TUP-60	60W	60W±10%	175-265V	1215*75*25
HEC-TUP-70	70W	70W±10%	175-265V	1215*75*25
HEC-TUP-20	20W	20W±10%	110~265V	615*55*25
HEC-TUP-40	40W	40W±10%	170~265V	1215*55*25

Power Factor :0.55PF±10%  
 CCT:3000K/4000K/6500K  
 Material:Aluminum+Plastic  
 CRI:Ra>70  
 SMD Luminous:130lm/w  
 Beam Angle:180°



## APPLICATIONS:

WIDELY APPLICABLE TO INDOOR LOCATIONS, SUCH AS HOTELS, RESTAURANTS, OFFICES, SHOWROOMS, HOUSES AND SIMILAR PLACES.



BATTEN LIGHTS